



Brooktrout Fax Products

Documentation Update

SDK Version 6.14.0

January 2021

Terms of Use

Any software (“Software”) that is made available by Enghouse Interactive Inc. (“Enghouse”), together with any User Documentation (“User Documentation”) is the copyrighted work of Enghouse. Use of the Software is governed by the terms of a Master Purchase Agreement, End User License Agreement, or similar software license agreement (“License Agreement”). End users are not legally authorized to install any Software that is accompanied by or includes a License Agreement unless he or she first agrees to the License Agreement terms.

The Software is made available for installation solely for use by users according to the License Agreement. Any reproduction or redistribution of the Software not in accordance with the License Agreement is expressly prohibited by law and may result in severe civil and criminal penalties. Violators will be prosecuted to the maximum extent possible.

WITHOUT LIMITING THE FOREGOING, COPYING OR REPRODUCTION OF THE SOFTWARE TO ANY OTHER SERVER OR LOCATION FOR FURTHER REPRODUCTION OR REDISTRIBUTION IS EXPRESSLY PROHIBITED, UNLESS SUCH REPRODUCTION OR REDISTRIBUTION IS EXPRESSLY PERMITTED BY THE LICENSE AGREEMENT ACCOMPANYING SUCH SOFTWARE.

THE SOFTWARE IS WARRANTED, IF AT ALL, ONLY ACCORDING TO THE TERMS OF THE LICENSE AGREEMENT. ENGHOUSE HEREBY DISCLAIMS ALL OTHER NON-EXPRESS WARRANTIES AND CONDITIONS WITH REGARD TO THE SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES AND CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NON-INFRINGEMENT.

Enghouse grants a nonexclusive license to customer for use of the User Documentation. The User Documentation contains copyrighted and other proprietary materials. By accepting the User Documentation, recipients agree that they will not transmit, reproduce, or make available to any external third-party this User Documentation or any information contained herein. Copying, reverse-engineering, or reselling any part of the Software or User Documentation is strictly prohibited.

The information contained in the User Documentation furnished by Enghouse is based on the most accurate information available at the time of printing. No representation or warranty is made by Enghouse as to the accuracy or completeness of such information or any ongoing obligation to update such information. Enghouse reserves the right to change the information contained in this document without notice.

Table of Contents

Purpose.....	3
Advanced SIP IP Call Control Stack Parameters.....	4
Configuring T.38 Fax Transport Parameters.....	5
BfvFaxT30Holdup.....	8
BfvLineOriginateCall and BfvCallSetup.....	9
BfvLineOriginateCall and BfvCallWaitForComplete.....	10

Purpose

The purpose of this document is to capture the documentation changes for the SDK 6.14.0 release. Specifically, it provides the information on the changes to the SDK 6.13.0 version of the Dialogic Brooktrout Bfv APIs Reference Manual. The changes in this document will be incorporated into the API Reference Manual to be published at a future date.

Technical Support

For Technical Support, see www.dialogic.com/support

Product Documentation

For the latest product documentation, see <https://www.dialogic.com/manuals/brooktrout/brooktrout>.

Advanced SIP IP Call Control Stack Parameters

The following items to be added to Table 27 on page 1276.

Key Name	Description
<i>ignore_non_initial_record_route</i>	<p>This parameter is used to ignore or recognize non-initial record routes from incoming SIP messages.</p> <p>The following are the allowable parameter values:</p> <p>TRUE Ignore non-initial record routes FALSE Recognize non-initial record routes</p> <p>Note: This parameter should only be used when directed to do so by Dialogic Technical Services and Support.</p> <p>Default: FALSE</p>
<i>sip_use_any_reg_contact_expire</i>	<p>This parameter is used determine the behavior of the session timeout relating to the REGISTER mesasage.</p> <p>The following are the allowable parameter values:</p> <p>TRUE The URI(s) that appear in the Contact: must match on the Contacts in the REGISTER message for the “expires=” value to be accepted FALSE The URI(s) do not need to match</p> <p>Note: This parameter should only be used when directed to do so by Dialogic Technical Services and Support.</p> <p>Default: TRUE</p>

Configuring T.38 Fax Transport Parameters

The text of the *media_renegotiate_delay_inbound*, *media_passthrough_timeout_inbound*, *media_renegotiate_delay_outbound* and the *media_passthrough_timeout_outbound* parameters starting on page 1239 to be replaced with the text below:

Parameter	Value						
<i>media_renegotiate_delay_inbound</i>	<p>Controls media renegotiation to image (T.38) on inbound calls. If the gateway is responsible for media renegotiation, set this parameter to -1 and [fax_transport_protocol] to t38_only to disable initiating the media renegotiation to image. Setting this parameter to -1 and [fax_transport_protocol] to t38_first will cause the inbound side renegotiation to T.38 being controlled by [media_passthrough_timeout_inbound].</p> <p>If the inbound side is responsible for media renegotiation to image, set this parameter to a value between 0 and 60000.</p> <p>Numbers from 0 to 3000 will cause the inbound side to renegotiate to T.38 after 3 seconds.</p> <p>Numbers from 3000 to 60000 indicate the number of milliseconds to delay before the inbound side attempts media renegotiation to T.38.</p> <p>Set this parameter to:</p> <table> <tr> <td>1</td> <td>Disables media renegotiation on inbound calls if [fax_transport_protocol] is t38_only. See [media_passthrough_timeout_inbound] if [fax_transport_protocol] is t38_first.</td> </tr> <tr> <td>0 to 3000</td> <td>Waits 3 seconds before attempting to renegotiate the media to T.38.</td> </tr> <tr> <td>3000 to 60000</td> <td>Waits this number of milliseconds before attempting to renegotiate the media to T.38.</td> </tr> </table> <p>Unit: ms Range: -1 and 0 to 60000 Value Type: decimal Default: 3000 (3 seconds)</p>	1	Disables media renegotiation on inbound calls if [fax_transport_protocol] is t38_only. See [media_passthrough_timeout_inbound] if [fax_transport_protocol] is t38_first.	0 to 3000	Waits 3 seconds before attempting to renegotiate the media to T.38.	3000 to 60000	Waits this number of milliseconds before attempting to renegotiate the media to T.38.
1	Disables media renegotiation on inbound calls if [fax_transport_protocol] is t38_only. See [media_passthrough_timeout_inbound] if [fax_transport_protocol] is t38_first.						
0 to 3000	Waits 3 seconds before attempting to renegotiate the media to T.38.						
3000 to 60000	Waits this number of milliseconds before attempting to renegotiate the media to T.38.						
<i>media_passthrough_timeout_inbound</i>	<p>Sets the time before media renegotiation to image (T.38) will be attempted before doing fax passthrough on inbound calls. This timer is active only when [media_renegotiate_delay_inbound] is set to -1, [fax_transport_protocol] is set to t38_first and the module supports fax passthrough.</p> <p>Setting this parameter to -1 will suppress the sending of a REINVITE to T.38 and fax passthrough.</p>						

	<p>Numbers from 0 to 3000 will cause the inbound side to wait 3 seconds before attempting media renegotiation to image (T.38).</p> <p>Numbers from 3000 to 60000 indicate the number of milliseconds to delay before attempting media renegotiation to image (T.38).</p> <p>Set this parameter to:</p> <p>-1 Suppress renegotiation to T.38 or fax passthrough. 0 to 3000 Waits 3 seconds before attempting renegotiation to T.38 and fax passthrough. 3000 to 60000 Number of milliseconds to wait before attempting renegotiation to T.38 and fax passthrough.</p> <p>Unit: ms Range: -1 and 0 to 60000 Value Type: decimal Default: 3000 (3 seconds)</p>
<i>media_renegotiate_delay_outbound</i>	<p>Controls media renegotiation to image (T.38) on outbound calls. If the gateway is responsible for media renegotiation, set this parameter to -1 to disable initiating the media renegotiation to image.</p> <p>If the outbound side is responsible for media renegotiation to image, set this parameter to a value between 0 and 60000. Numbers greater than 0 indicate the number of milliseconds to delay before attempting media renegotiation.</p> <p>A value of 0 will cause an immediate renegotiation, while -1 will wait for a renegotiation to image.</p> <p>Set this parameter to:</p> <p>-1 Disables media renegotiation on outbound calls. 0 Does not delay before attempting to renegotiate the media to image (T.38). >0 Waits this number of milliseconds before attempting to renegotiate the media to image (T.38).</p> <p>Unit: ms Range: -1 and 0 to 60000 Value Type: decimal Default: -1</p>
<i>media_passthrough_timeout_outbound</i>	<p>Sets the timer to fail over to fax passthrough when no T.38 is negotiated on outbound calls. This timer is active only when [media_renegotiate_delay_outbound] is set to -1, [fax_transport_protocol] is set to t38_first and the module supports fax passthrough.</p> <p>Numbers greater than 0, indicate the number of milliseconds to wait for T.38 negotiation before performing fax passthrough. A value of 0</p>

	<p>will cause an immediate renegotiation to passthrough, while -1 will suppress renegotiation to fax passthrough.</p> <p>Set this parameter to:</p> <ul style="list-style-type: none">-1 Suppress renegotiation to fax passthrough.0 Cause an immediate renegotiation to passthrough.>0 Number of milliseconds to wait for T.38 negotiation before performing fax passthrough. <p>Unit: ms</p> <p>Range: -1 and 0 to 60000</p> <p>Value Type: decimal</p> <p>Default: 4000</p>
--	---

BfvFaxT30Holdup

In the last paragraph on page 758, the following text:

The receiver responds with a signal which is typically MCF, though it could also be RTN, RTP, PIN, or PIP.

to be replaced with:

The receiver responds with a signal which is typically MCF, though it could also be ERR, RTN, RTP, PIN, or PIP.

BfvLineOriginateCall and BfvCallSetup

The following Input Field to be added to BfvLineOriginateCall on page 374 and BfvCallSetup on page 303.

```
enum TPerCallFaxTransportProtocol per_call_fax_transport_protocol;
```

per_call_fax_transport_protocol - Allows restriction of the fax transport protocol on a per-call basis.

The value can be one of the following:

PER_CALL_FAX_TRANSPORT_PROTOCOL_DEFAULT (0) - The fax transport protocol will be determined based on the call control configuration file settings.

PER_CALL_FAX_TRANSPORT_PROTOCOL_RTP_PREFERRED (1) - The fax transport protocol will be G.711 (RTP), if available, regardless of the call control configuration file settings; if not, it will be T.38.

BfvLineOriginateCall and BfvCallWaitForComplete

The Output fields for BfvLineOriginateCall on page 374 and BfvCallWaitForComplete on page 377 to be changed to:

```
int cause;
int subcause;
int cause_location;
RES res;
CALL_RES cres.name_ident;
CALL_RES cres.name_char_set;
CALL_RES cres.connected_num;
CALL_RES cres.sip_call_id
enum TRxTransportType call_transport;
unsigned sip_header_list_len;
BT_SIP_HEADER_LIST *sip_header_list;
```

In the description section, the following text to be added:

args.cres.char sip_call_id

Returns text in the sip_call_id field of the CALL_RES structure (see Volume 6, Appendix B, CALL_RES Structure Parameters), indicating the SIP Call-ID when using the SIP protocol. The field allows a maximum of 256 characters(MAX_SIP_CALL_ID).

In **Appendix B - Bfv API Structures** section, in "**Result Structures**" section on page 1335 the CALL_RES structure to be updated to the following:

```
typedef struct {
    int call_type;
    char dest_id[MAX_DID];
    /* The rest are ISDN only */
    #define called_party_number dest_id
    char called_party_subaddress[MAX_DID];
    char calling_party_number[MAX_DID];
    char calling_party_subaddress[MAX_DID];
    char redir_number[MAX_DID];
    int redir_reason;
    char name_ident;
    int name_char_set;
    char connected_num[MAX_CONN_NUM];
    char sip_call_id[MAX_SIP_CALL_ID]
} CALL_RES;
```

In "**CALL_RES Structure Parameters**" on page 1343, the following to be added:

sip_call_id

A null-terminated ASCII string that identifies the SIP Call-ID. This value is only indicated for the SIP protocol.